



W75

PRODUCT INFORMATION

- OIML R76:2006 Class III 10,000 Division Type Approved and EN45501:2015 Ready
- Extra Large 50mm Digit Size Wide Angle LCD Display with LED Backlight
- Heavy Duty Construction Design Withstand Harsh Industrial Operation
- Overload and Shock Protection
- High Speed 24 bits Multiplexed Delta-Sigma A/D Converter
- Approved Dual Weighing Range
- Supporting kg/lb Conversion and Simple Piece Counting
- Functions Including: Power On Zero Tracking, Manual Zero, Full Subtractive Tare, Auto Tare, Preset Tare, Automatic Continuous Tare, Data Accumulation, Digital Motion Filtering, Animal Weighing, Piece Counting, Checkweighing, HI-OK-LO Buzzer and Battery Power Level Indicator
- Built-in Rechargeable Battery for 210 Hours Operating Time
- Platter size: 400 x 500 mm

Model	Capacity x Readability
W75-F60	30/60kg x 0.01/0.02kg
W75-F150	60/150kg x 0.02/0.05kg
W75-F300	150/300kg x 0.05/0.1kg
Operating Environment	10°C ~40°C (14°F ~104°F), Non-condensed. R.H. ≤85%
Power Source	By Built-in Rechargeable Battery or Power Adaptor
Options Available	RS232 Interface, RS485, Real Time Clock, 4 Channels Relay Output



UNIVERSAL WEIGHT ELECTRONICS CO., LTD.

📍 4th FLOOR, NO.53, BAOXING ROAD, XINDIAN DISTRICT, NEW TAIPEI CITY 231, TAIWAN (R.O.C)

+886-2-29180121 (12Lines)

int@uwe.com.tw

www.uwe.com.tw