



WSK SERIES

FEATURES

- User Programmable Display Resolution(Dual interval, up to 1/30,000)
- All Stainless Steel Housing, IP67
- 7-Segment LED Display (Weight : 6 digits, High-Limit & Low-Limit : 5 digits)
- Multi Segment Traffic Display for HI-OK-LO Status (Orange/Green/Red LED * 24pcs)
- Selectable Audible tone(Accept, Under, Over, Under/Over, no beep)
- 4 Traffic Display Mode (Bar1~Bar4) to meet variety of Applications
- Limit Setting Via RS-232
- Bi-Directional RS-232 Transmission, Offers different data output options
- 30 Sets of Set Point Data (HI & LO LIMIT, Pre-Tare)
- UTP printer Compatible
- Built-in Calendar IC, can print out Date, Time Information
- Password Protected for System Parameters and PLU data
- All-in-one with Weighing, Counting, Checking, Stocklive Weighing Functions
- AC100V~240V Selection-Free Power Input



SPECIFICATIONS

Model No.	Capacity (Max)	Division (e)
WSK Indicator	Freely Programmable	Freely Programmable
Tare Range	Full Tare Range	
Power-on Zero Range	Selectable with 0%、2%、10%、20%、50%、100% FS	
Zero Range	Selectable with 0%、2%、10%、20%、50%、100% FS	
Min. Load	20e	
Weighing Unit	kg、lb、User Defined	
Power Source	AC Power Input 100V~240V	
Operating Environment	0° ~ 40° C / (32° ~ 104° F) Non-condensed.R.H.≤85%	

OPTION :

1. RS-232 Interface (Included in standard product)
2. Relay Output